

B2X-23P Portable



DATA SHEET

MID-RANGE 2-STAGE FIRE PUMP

Designed for OEM Fire Apparatus Manufacturers who need a vehicle mounted pump the **WATERAX B2X** is a versatile Mid-Range portable pump that delivers the best performance of its class with minimal operating costs. Unlike other pumps, the **B2X** uses a low maintenance drive belt system that provides efficient and dependable performance.

The **WATERAX B2X-23** pump pairs a reliable high performance Mid-Range 2-stage pump end with a powerful Briggs & Stratton 4-stroke 23 hp engine to achieve pressures of up to 200 PSI (13.8 BAR) and flow rates reaching 300 GPM (1136 L/Min). A strong show of both pressure and volume makes it the ideal pump for vehicle mounted applications dedicated to municipal and wildland urban interface operations.

The **WATERAX** quick release clamp provided on the **B2X** pump provides ease of maintenance without having to disassemble the complete pump unit thus significantly reducing equipment downtime.


Applications

- Structure attack lines firefighting
- Tandem pumping over long distance
- Parallel pumping for higher volumes
- 2x 1-1/2" simultaneous attack lines
- 2-1/2" high volume supply line
- Water transfer
- Tanker water fill / removal
- Portable tank fill
- Structure protection

Features and Benefits

- Quick release clamp and swappable pump ends for ease of maintenance and minimal equipment downtime.
- Belt drive system for reliable, low maintenance performance.
- Aluminum alloy pump components and anodized parts for lighter weight and greater resistance to corrosion
- Comprehensive user and service manuals
- EPA Certified

SPECIFICATIONS



Flow rate at specified pressure

Maximum Pressure: 200 PSI (13.8 bar)
 Free flow: 300 US gals/min (1136 L/min)
 Maximum Head: 462' (141 m)

Flow Rate		Pressure		
US GPM	(LPM)	@	PSI	(BAR)
288	(1090)	@	50	(3.4)
200	(757)	@	100	(6.9)
95	(360)	@	150	(10.3)

Engine: Briggs & Stratton® Vanguard™ - 23 hp



Pump Specifications:

Type:	Detachable 2-stage Centrifugal
Ratings:	ISO 9 and NFPA 1906 Medium Pressure Rating of 50 GPM
Description:	Medium Pressure, Medium Flow, Foam Compatible
Maximum Allowable Pressure:	400 PSI (27.6 bar)
Maximum Flow:	300 GPM (1136 lpm)
Intake:	3" NPT Female/4" Victaulic Combination (Other options available thru adapters)
Discharge:	2-1/2" NPT Female/3" Victaulic Combination (Other options available thru adapters)
Body & Diffusers:	Anodized corrosive resistant aluminum
Impellers:	4.00" Diameter; Anodized corrosive resistant aluminum
Pump Shaft:	Stainless Steel
Bearings:	Maintenance Free; sealed ball bearing and sintered bronze sleeve
Pump Seal:	Maintenance Free; Blister-resistant carbon seal face, silicon carbide seat, and fully integrated drive bushing.
Clamp:	Hand tight quick release clamp [no tools needed]
Drive Unit:	Timing Belt and Pulley; Speed Increaser
Speed Increaser Position:	Vertical
Drive Ratio:	1.88: 1
Color:	Red
Special Feature:	The entire pump separates completely from the engine/speed increaser.

Engine Specifications:

Model & Type:	Briggs and Stratton Vanguard 4-cycle, horizontal shaft, twin cylinder, OHV
Maximum Power:	23 HP (17.2 kW) @ 3600 RPM
Maximum Torque:	32.75 lb-ft (44.4 Nm) @ 2600 RPM
Bore & Stroke:	2.97 x 2.76 inches (72 x 70 mm)
Displacement:	38.26 cubic inches (627 cc)
Starting System:	Re-coil start with 12 VDC electric start option
Ignition:	Magnatron
Charging:	16 AMP regulating alternator
Governor:	Mechanical
Cooling:	Air Cooled
Lubrication:	Oil, Full pressure
Oil Capacity:	1.8 quarts (1.7 liters)
Fuel Pump:	18 inch lift.
Emissions:	Meets current CARB, EPA, and CE requirements.
Fuel Type:	Gasoline [unleaded, 86 minimum octane, 10% maximum ethanol]
Fuel Consumption:	2.1 US gals/hr (7.9 liters/hr)
Muffler:	Forestry approved spark arrestor

All features are not available on every model. Please refer to the product selection matrix to select the proper model.



**WE MOVE
WATER**

SPECIFICATIONS

Primer Specifications:

Hand Primer Option:

	Guzzler, Diaphragm Type; Reliable, Lightweight and Rugged
Intake and Discharge Port Size:	½" Female NPT
Construction:	Aluminum Handle, composite body, buna-n reinforced diaphragm and flapper valves
Lift:	12 feet (3.7 m) [up to approximately 16 feet (4.8 m) with suction hose footvalve]
Head Capacity:	30 ft (9.1 m)
Maximum Pressure:	15 PSI (1.03 bar)
Maximum Service Temp:	150° F (66° C)
Volume per Stroke:	0.44 quart (0.42 liter)
Dimensions (L x W x H):	12-3/4" x 4-1/2" x 4-5/16" (324 x 114 x 110 mm)
Weight:	1.70 lbs (0.77 kg)
Location:	Mounted on starter side of engine

Exhaust Primer Option:

	Venturi Type (when selected mounted to exhaust primer muffler)
Venturi Construction:	Brass
Exhaust Valve Construction:	Aluminum with stainless shaft and disc
Operation:	Remote mount push/pull cable.
Vacuum:	Minimum of 17 in-Hg
Location:	Mounted on the vertical exhaust muffler; starter side of engine.

Electric Primer Option:

	12 VDC Piston Type Vacuum Pump
Intake and Discharge Port Size:	3/8" Female NPT
Construction:	Corrosion Resistant Aluminum with Bronze Sleeve and Composite Piston
Max. Current Draw:	105 amps
Lift:	25 feet (7.6 m)
Vacuum:	22 in-Hg
Dimensions:	9" x 4-1/8" x 7-1/2" (229 x 105 x 191 mm)
Weight:	8.1 lbs (3.7 kg)
Location:	Mounted on starter side of engine

Frame Specifications:

Color:	Black
Finish:	Powder Coat
Handles:	Tubular U-shaped integrated into the base frame

Controls Specifications:

Briggs & Stratton Standard Engine Controls:

Start/Stop:	Turn-key rotary switch
Throttle:	Lever control on left side of blower housing
Choke:	Push/pull ring pin located on starter side of the engine below the air filter housing.

Engine Mount Control Panel:

On/Off Switch:	Weather resistant chrome toggle switch
Start:	Weather resistant push button switch (with battery kit option only)
Throttle:	Vernier with red push button emergency throttle idle
Low Oil Pressure Warning:	Red LED (with battery kit option only)
Choke:	Push/pull ring pin located on starter side of the engine below the air filter housing.

Discharge Gauge Specifications:

0 to 600 PSI Dual unit (PSI/kilopascals) liquid filled; Pump mounted.

All features are not available on every model. Please refer to the product selection matrix to select the proper model.



**WE MOVE
WATER**

PRODUCT SELECTION

PRODUCT SELECTION MATRIX

		B2X-23P	B2X-23PC	B2X-23PXC	B2X-23PETC	
STANDARD INCLUSIONS	Primer	Guzzler Hand Primer	S	S	-	-
		Remote Exhaust Primer w/Control Cable PART-763	-	-	-	-
		Exhaust Primer	-	-	S	-
		Electric Package - Electric Primer, LED work light, & Battery	-	-	-	S
	Muffler	Horizontal low tone	-	-	-	-
		Dual B&S low tone	S	S	-	-
		Exhaust primer muffler	-	-	S	S
	Fuel Tank	Integral / 7 US qts (6.6 L)	-	-	-	-
		Integral / 4 US qts (3.8 L) w/ 3-way valve	-	-	S	S
	Controls	Engine Mount Control Panel	-	S	S	S
	Discharge Gauge	0-600 psi, 2-1/2" dial	S	S	S	S
	Check Valve Manifold	B&S 3' CTRL Cable with 8 pin connector (FWC-B-3)	-	-	-	-
FastWire CTRL Cable	Honda GX630 3' CTRL Cable with 8 pin connector (FWC-H-3)	-	-	-	-	
Weight		167 lbs (76 kg)	169 lbs (77 kg)	170 lbs (77 kg)	195 lbs (88 kg)	

OPTIONS & ACCESSORIES

Sold Separately

Electric Kit



BATKIT-20-P
Battery Kit 12V 20ah, Portable



WLIGHTKIT
LED Work Light w/ 5' harness & toggle switch

Fuel Tank & Fuel Line



FA-452
Remote Fuel Tank
6.6 US Gallons w/ quick conn.

FA-452-3
Remote Fuel Tank
3.2 US Gallons w/ quick conn.

12-401B-NS-TRPD
Fuel Line EPA -
quick conn. to hose 1/4"

12-401B-NS-TRPD
Fuel Line -
quick conn. to SAE 45 Flare

Pump Intake & Discharge Adapters

B2X-CONVKIT
B2XRK1
B2X-PVKIT

B2 TO B2X CONVERSION KIT
SEAL KIT FOR B-2 & B2X
B2X PRIMER VALVE KIT



ADP-B2X-25N25N
ADP-B2X-30N25N
RED-24255252
RED-24255253
PART-520
PART-521
PART-522
PART-523

ADP KIT B2X,SUC 2.5,DIS 2.5 NH
ADP KIT B2X,SUC 3.0,DIS 2.5 NH
WYE VALVE 2.5NH F X 1.5NPSH M
WYE VALVE 2.5NH F X 1.5NH M
GROOVED COUPLING 3",GALV.
GROOVED COUPLING 4",GALV.
GROOVED CPLG 3 TO 2.5",GALV.
GROOVED CPLG 4 TO 3",GALV.






**WE MOVE
WATER**

TECHNICAL DRAWINGS




B2X-23P

Length 35" (88.9 cm) Width 19.75" (50.16 cm) Height 20.5" (52.07 cm) Weight 167 lbs (76 kg)






B2X-23PC

Length 35" (88.9 cm) Width 19.75" (50.16 cm) Height 20.5" (52.07 cm) Weight 169 lbs (77 kg)






B2X-23PXTC

Length 35" (88.9 cm) Width 22" (55.88 cm) Height 20.5" (52.07 cm) Weight 170 lbs (77 kg)



B2X-23PETC

Length 35" (88.9 cm) Width 22" (55.88 cm) Height 23.25" (59.05 cm) Weight 195 lbs (88 kg)



**WE MOVE
WATER**

WATERAX

All information contained in this document including drawings is proprietary to *WATERAX* and may not be copied, reproduced or used in whole or in part without our prior written permission. The information in this document is subject to change without notice. Model displayed with multiple options. Weight and dimensions are approximated and may vary depending on options.

WATERAX INC.

6635 Henri-Bourassa W.
Montreal, QC H4R 1E1

T 514 637-1818

F 514 637-3985

TF 1 855 616 616-1818

info@waterax.com

waterax.com

To help you stay **#ReadyForWildfires**, we've made a few changes, placing 100% of our focus on manufacturing our core products, portable fire pumps.

To do so, we've established a network of trusted supply and distribution partners that can help us provide *WATERAX* pumps quickly in addition to water-handling equipment and accessories.

For immediate assistance when it comes to pumps and water-handling accessories, please contact your local dealer.

For genuine spare parts, visit our online store.

B2X™ is a trademark of Waterax.



**WE MOVE
WATER**