



# StreamMaster II Monitor

## STYLE 3480 & 3482 2000 GPM (7600 LPM)

With its patented design, the StreamMaster II provides efficient flows up to 2000 gpm (7600 lpm) in a compact configuration. The unique waterway design provides balanced forces on the outlet which results in the fastest speeds, longer life, and reduced friction leading to exceptional stream performance.

- Compact industry-leading operating envelope (6", 152 mm)
- Fastest speeds
- Superior range of motion
  - Rotation Range 355°
  - Elevation Range +120°, - 45°
- Simple "plug and play" installation
- Integrated wireless compatibility
- Override hand-wheels
- Absolute position sensors
- Programmable functions; obstacle avoidance, ladder avoidance, oscillation and stow and deploy positions
- Waterproof (IP 67 rated) onboard, fully sealed control system with locking connectors
- Compatible with 3406 Electric Riser
- Cloning for easy programming & USB port for quick software updates in the field



STYLE 3480  
With 5178  
Nozzle

Style	Weight lbs. (kg)	Height	Width	Depth	Inlet	Outlet	Flow	
							GPM	LPM
3480	44.2 (20.1 kg)*	16" (400 mm)	11 1/8" (295 mm)	17" (430 mm)	4" Flange (DN100)	3 1/2" Male (89 mm)	2000	7600
3482	41.7 (19.9 kg)*	16" (400 mm)	11" (280 mm)	16 1/8" (410 mm)	3" Flange (DN80)	2 1/2" Male (65 mm)	1250	4800

\* Less nozzle

## STYLE 3486 Aerial Valve Manifold (AVM)

The industry-leading StreamMaster II (SMII) is now available as a complete package with a valve manifold to control the flow of water and allow for extension of hose lines from a platform or ladder. The SMII is a compact, lightweight total solution that comes ready to install on the apparatus. There is virtually no additional friction loss through the main valve which provides advantages over a butterfly valve when you need to get the most flow possible from your aerial device.

- Integrated ball valve to control flow of water to the monitor with manual gear actuator
- Available with Electric or Manual StreamMaster II
- 90° discharge valve with 2 ½” NH threads for extension of hose
- ¼ turn ball valve for smooth operation of discharge valves
- Integrated, one piece solution – ships complete with AVM attached to StreamMaster II
- Valve extension comes standard with 1” NPT port for customer supplied pressure relief valve if desired)
- Available in 5 standard AVM configurations (shown with electric StreamMaster II)



STYLE 3486  
With 5178  
Nozzle

### NOZZLE OPTIONS



### CAN CONTROL OPTIONS

