

# AIRPOWER® XR23


Art. No. 607903



## ASTM F2413-2018 M /I/C, CSA Z 195-2014 Grade 1

Split leather brown 2.0 – 2.2 mm, GORE-TEX Insulated, leg height 7 inch, sole 012

Available sizes US 4 ½ – 15



HAIX® Climate System



607903



### Upper Material

Split leather, hydrophobic and breathable (5,0mg/cm<sup>2</sup>/h), 2.0 – 2.2 mm thick

### Inner Lining

GORE-TEX Insulated Comfort footwear combines durable waterproofing and breathability with protection from cold temperatures. This ensures dry and warm wearing comfort and makes them particularly suitable for working in harsh weather conditions.

### Non-woven insole

Non-woven insole absorbs moisture.

### Foot bed

For extra foot comfort and impact-absorbing and moisture-wicking. Separate heel cup ensures optimized cushioning and foot guidance. "AIRFLOW" channels.

### HAIX® Protective sole

Flexible, lightweight and puncture resistant textile throughsole.

### HAIX® Protective toe cap

Anatomically formed and ultralight protective toe cap made of fiber-reinforced plastic for highest safety requirements.

### Sole

Anti-slip rubber/PU sole with road/off-road profile, abrasion-proof, for enhanced toe-to-heel support, ideal for cold weather conditions. The lightweight PU cushioning wedge provides optimum wear comfort. Excellent thermal insulation. The nonmarking outer sole is resistant to heat, oil and gasoline.

### HAIX® Climate System

The HAIX® Climate system uses the pumping movement, which permits air circulation with every step – warm air is released and fresh air comes in through the vent holes at the top of the boot.

### HAIX® AS System

The HAIX® Arch Support System supports the natural curvature of the foot. Toes and joints have thereby sufficiently more space. Keeps foot in the best position for optimal foot health.

### Others

Low friction lacing elements of high quality, padded shaft, TPU-toe cap. Electrical hazard resistant to 18 kV acc. to ASTM F2413-18 and CSA Z195-2014.

UK	3	3½	4	4½	5	5½	6	6½	7	7½	8	8½	9	9½	10	10½	11	11½	12	12½	13	13½	14	14½	15
EU	35	36	37	37	38	39	39	40	41	41	42	43	43	44	45	45	46	47	47	48	48	49	50	50	51
US	4	4½	5	5½	6	6½	7	7½	8	8½	9	9½	10	10½	11	11½	12	12½	13	13½	14	14½	15	15½	16

### HAIX® North America Inc.

2320 Fortune Drive, Suite 120, Lexington, KY 40509  
 Phone 859-281-0111, Fax 859-281-0113  
 Toll free 866-344-HAIX (4249), www.haix.com