

ARMTEX® ATTACK LITE™

Lightweight All-Polyester Double Jacket
Polyurethane Lined Fire Hose

COLORS:



General Applications:

- Municipal fire departments
- Industrial fire brigades
- High rise packs

Construction:

Double-jacket polyester hose with a polyurethane lining. Jacket color options include blue, green, black, orange, purple, red, tan, white and yellow.

Service Temperature Range:

Remains flexible at temperatures as low as -40°F (-40°C).

Features and Advantages:

- High Burst Rating – 1,200 psi up to 3" diameter.
- Superior Performance – Very low friction loss.
- ARMTEX® ATTACK LITE™ is available in the sizes of 1 1/2", 1 3/4", 2", 2 1/2" and 3".
- Packs Tight – KFP's best packing and easiest to fold double-jacket hose.
- Maintenance Free – Immune to mildew and rot.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- 10-year warranty.

Packaging:

Available in 25', 50' and 100' lengths.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Lightweight All-Polyester Double Jacket Polyurethane Lined Fire Hose

Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
AL150BXXX-NH150	1 1/2	Blue	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150BXXX-NP150	1 1/2	Blue	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL150GXXX-NH150	1 1/2	Green	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150GXXX-NP150	1 1/2	Green	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL150LXXX-NH150	1 1/2	Black	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150LXXX-NP150	1 1/2	Black	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL150OXXX-NH150	1 1/2	Orange	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150OXXX-NP150	1 1/2	Orange	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL150PXXX-NH150	1 1/2	Purple	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150PXXX-NP150	1 1/2	Purple	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL150RXXX-NH150	1 1/2	Red	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150RXXX-NP150	1 1/2	Red	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL150TXXX-NH150	1 1/2	Tan	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150TXXX-NP150	1 1/2	Tan	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL150WXXX-NH150	1 1/2	White	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150WXXX-NP150	1 1/2	White	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL150YXXX-NH150	1 1/2	Yellow	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
AL150YXXX-NP150	1 1/2	Yellow	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
AL175BXXX-NH150	1 3/4	Blue	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175BXXX-NP150	1 3/4	Blue	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30
AL175GXXX-NH150	1 3/4	Green	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175GXXX-NP150	1 3/4	Green	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30
AL175LXXX-NH150	1 3/4	Black	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175LXXX-NP150	1 3/4	Black	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30
AL175OXXX-NH150	1 3/4	Orange	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175OXXX-NP150	1 3/4	Orange	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30
AL175PXXX-NH150	1 3/4	Purple	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175PXXX-NP150	1 3/4	Purple	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30
AL175RXXX-NH150	1 3/4	Red	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175RXXX-NP150	1 3/4	Red	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30
AL175TXXX-NH150	1 3/4	Tan	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175TXXX-NP150	1 3/4	Tan	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Lightweight All-Polyester Double Jacket Polyurethane Lined Fire Hose

Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
AL175WXXX-NH150	1 3/4	White	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175WXXX-NP150	1 3/4	White	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30
AL175YXXX-NH150	1 3/4	Yellow	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.30
AL175YXXX-NP150	1 3/4	Yellow	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.30
AL200BXXX-NH150	2	Blue	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200BXXX-NP150	2	Blue	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL200GXXX-NH150	2	Green	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200GXXX-NP150	2	Green	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL200LXXX-NH150	2	Black	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200LXXX-NP150	2	Black	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL200OXXX-NH150	2	Orange	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200OXXX-NP150	2	Orange	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL200PXXX-NH150	2	Purple	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200PXXX-NP150	2	Purple	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL200RXXX-NH150	2	Red	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200RXXX-NP150	2	Red	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL200TXXX-NH150	2	Tan	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200TXXX-NP150	2	Tan	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL200WXXX-NH150	2	White	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200WXXX-NP150	2	White	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL200YXXX-NH150	2	Yellow	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AL200YXXX-NP150	2	Yellow	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AL250BXXX-NH250	2 1/2	Blue	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL250GXXX-NH250	2 1/2	Green	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL250LXXX-NH250	2 1/2	Black	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL250OXXX-NH250	2 1/2	Orange	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL250PXXX-NH250	2 1/2	Purple	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL250RXXX-NH250	2 1/2	Red	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL250TXXX-NH250	2 1/2	Tan	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL250WXXX-NH250	2 1/2	White	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL250YXXX-NH250	2 1/2	Yellow	2 1/2	NST	3	400	800	1200	25/50/100	0.46
AL300BXXX-NH250	3	Blue	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Lightweight All-Polyester Double Jacket Polyurethane Lined Fire Hose

Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
AL300GXXX-NH250	3	Green	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53
AL300LXXX-NH250	3	Black	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53
AL300OXXX-NH250	3	Orange	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53
AL300PXXX-NH250	3	Purple	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53
AL300RXXX-NH250	3	Red	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53
AL300TXXX-NH250	3	Tan	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53
AL300WXXX-NH250	3	White	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53
AL300YXXX-NH250	3	Yellow	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.53

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.