Dixon Northline Siamese Connectors

Application:

This lightweight, compact siamese connection is used to supply a large diameter hose from two smaller lines.

Features:

- can be used to distribute water in the opposite direction by removing the clapper valves
- comes standard with clapper (removable if required), Storz connection outlet and 2, 3, or 4 21/2" Storz or female swivel inlets
- up to 280 PSI working pressure at 70°F (21°C)
- water way: 2, 3 o 4 inlet side 2½" maximum, 1 outlet 4½" maximum
- material: high strength aluminum alloy, 356-T6
- finish hardcoat anodized throughout minimum thickness 0.001"

2-Way Siamese Connectors

Outlet Storz	(2) Inlet	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
4"	2½" Female Swivel	FSSV4251	9.50"	9.25"	6.0"	8.0
5"	2½" Female Swivel	FSSV5251	10.00"	9.00"	7.5"	9.5
6"	2½" Female Swivel	FSSV6251	10.00"	9.00"	8.0"	9.5
4"	2½" Storz	SSV425	8.75"	9.50"	6.0"	8.0
5"	2½" Storz	SSV525	9.50"	9.50"	7.5"	9.0
6"	2½" Storz	SSV625	10.25"	9.50"	9.0"	10.0



3-Way Siamese Connectors

Outlet Storz	(3) Inlet	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
4"	2½" Female Swivel	FSSV3-4251	12.50"	13.75"	7.5"	15.0
5"	2½" Female Swivel	FSSV3-5251	12.50"	13.75"	8.0"	16.5
6"	2½" Female Swivel	FSSV3-6251	12.50"	13.75"	8.0"	17.0
4"	2½" Storz	SSV3-425	11.50"	13.75"	7.5"	14.5
5"	2½" Storz	SSV3-525	11.50"	13.75"	8.0"	15.5
6"	2½" Storz	SSV3-625	11.50"	13.75"	8.5"	16.5



4-Way Siamese Connectors

Outlet Storz	(4) Inlet	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
4"	2½" Female Swivel	FSSV4-4251	13.50"	18.00"	7.5"	19.0
5"	2½" Female Swivel	FSSV4-5251	13.50"	18.00"	8.0"	19.5
6"	2½" Female Swivel	FSSV4-6251	13.50"	18.00"	8.0"	19.5
4"	2½" Storz	SSV4-425	12.50"	17.25"	7.5"	18.0
5"	2½" Storz	SSV4-525	12.50"	17.25"	8.0"	18.5
6"	2½" Storz	SSV4-625	12.50"	17.25"	8.5"	19.0





¹ Customer Thread (must specify) refer to legend on page 705

¹ Customer Thread (must specify) refer to legend on page 705

¹ Customer Thread (must specify) refer to legend on page 705