


## All Polyester, Double-Jacket Fire Hose With Polyurethane Lining

### COLORS:



### General Applications:

- Municipal fire departments
- Industrial fire brigades
- Attack and supply lines
- High rise packs

### Construction:

**Double-Jacket Construction** – Jafline® is an all polyester double-jacket hose with a polyurethane lining.

### Service Temperature Range:

All-weather performance – Retains pliability to -40°F (-40°C).

### Features and Advantages:

- High Burst Rating – 1,200 psi up to 3" diameter, 900 psi for larger diameters.
- Superior Performance – Very low friction loss.
- Maintenance Free – Immune to mildew and rot.
- Coated for Better Durability – All colored hose is impregnated with our tough heat-set polymer coating for the best abrasion resistance.
- Very Lightweight – This is KFP's lightest weight American made hose. An uncoupled 1 1/2" 50' coil weighs just 14 lbs.
- Available in blue, green, black, orange, purple, red, tan, white and yellow.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- 10-year warranty.

### Packaging:

Available in 25', 50' and 100' lengths.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

## All Polyester, Double-Jacket Fire Hose With Polyurethane Lining

### Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
JL150BXXX-NH150	1 1/2	Blue	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150BXXX-NP150	1 1/2	Blue	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL150GXXX-NH150	1 1/2	Green	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150GXXX-NP150	1 1/2	Green	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL150LXXX-NH150	1 1/2	Black	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150LXXX-NP150	1 1/2	Black	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL150OXXX-NH150	1 1/2	Orange	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150OXXX-NP150	1 1/2	Orange	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL150PXXX-NH150	1 1/2	Purple	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150PXXX-NP150	1 1/2	Purple	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL150RXXX-NH150	1 1/2	Red	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150RXXX-NP150	1 1/2	Red	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL150TXXX-NH150	1 1/2	Tan	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150TXXX-NP150	1 1/2	Tan	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL150WXXX-NH150	1 1/2	White	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150WXXX-NP150	1 1/2	White	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL150YXXX-NH150	1 1/2	Yellow	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.28
JL150YXXX-NP150	1 1/2	Yellow	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.28
JL175BXXX-NH150	1 3/4	Blue	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175BXXX-NP150	1 3/4	Blue	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
JL175GXXX-NH150	1 3/4	Green	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175GXXX-NP150	1 3/4	Green	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
JL175LXXX-NH150	1 3/4	Black	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175LXXX-NP150	1 3/4	Black	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
JL175OXXX-NH150	1 3/4	Orange	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175OXXX-NP150	1 3/4	Orange	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
JL175PXXX-NH150	1 3/4	Purple	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175PXXX-NP150	1 3/4	Purple	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
JL175RXXX-NH150	1 3/4	Red	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175RXXX-NP150	1 3/4	Red	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
JL175TXXX-NH150	1 3/4	Tan	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175TXXX-NP150	1 3/4	Tan	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34

\*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

## All Polyester, Double-Jacket Fire Hose With Polyurethane Lining

### Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
JL175WXXX-NH150	1 3/4	White	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175WXXX-NP150	1 3/4	White	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
JL175YXXX-NH150	1 3/4	Yellow	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
JL175YXXX-NP150	1 3/4	Yellow	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
JL200BXXX-NH150	2	Blue	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200BXXX-NP150	2	Blue	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL200GXXX-NH150	2	Green	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200GXXX-NP150	2	Green	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL200LXXX-NH150	2	Black	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200LXXX-NP150	2	Black	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL200OXXX-NH150	2	Orange	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200OXXX-NP150	2	Orange	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL200PXXX-NH150	2	Purple	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200PXXX-NP150	2	Purple	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL200RXXX-NH150	2	Red	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200RXXX-NP150	2	Red	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL200TXXX-NH150	2	Tan	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200TXXX-NP150	2	Tan	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL200WXXX-NH150	2	White	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200WXXX-NP150	2	White	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL200YXXX-NH150	2	Yellow	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
JL200YXXX-NP150	2	Yellow	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
JL250BXXX-NH250	2 1/2	Blue	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL250GXXX-NH250	2 1/2	Green	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL250LXXX-NH250	2 1/2	Black	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL250OXXX-NH250	2 1/2	Orange	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL250PXXX-NH250	2 1/2	Purple	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL250RXXX-NH250	2 1/2	Red	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL250TXXX-NH250	2 1/2	Tan	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL250WXXX-NH250	2 1/2	White	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL250YXXX-NH250	2 1/2	Yellow	2 1/2	NST	3	400	800	1200	25/50/100	0.52
JL300BXXX-NH250	3	Blue	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74

\*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

## All Polyester, Double-Jacket Fire Hose With Polyurethane Lining

### Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
JL300GXXX-NH250	3	Green	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74
JL300LXXX-NH250	3	Black	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74
JL300OXXX-NH250	3	Orange	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74
JL300PXXX-NH250	3	Purple	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74
JL300RXXX-NH250	3	Red	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74
JL300TXXX-NH250	3	Tan	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74
JL300WXXX-NH250	3	White	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74
JL300YXXX-NH250	3	Yellow	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.74
JL400BXXX-SZ400	4	Blue	4	STORZ	4 17/32	300	600	900	25/50/100	0.82
JL400GXXX-SZ400	4	Green	4	STORZ	4 17/32	300	600	900	25/50/100	0.82
JL400OXXX-SZ400	4	Orange	4	STORZ	4 17/32	300	600	900	25/50/100	0.82
JL400RXXX-SZ400	4	Red	4	STORZ	4 17/32	300	600	900	25/50/100	0.82
JL400TXXX-SZ400	4	Tan	4	STORZ	4 17/32	300	600	900	25/50/100	0.82
JL400WXXX-SZ400	4	White	4	STORZ	4 17/32	300	600	900	25/50/100	0.82
JL400YXXX-SZ400	4	Yellow	4	STORZ	4 17/32	300	600	900	25/50/100	0.82
JL500BXXX-SZ500	5	Blue	5	STORZ	5 15/32	300	600	900	25/50/100	0.95
JL500GXXX-SZ500	5	Green	5	STORZ	5 15/32	300	600	900	25/50/100	0.95
JL500OXXX-SZ500	5	Orange	5	STORZ	5 15/32	300	600	900	25/50/100	0.95
JL500RXXX-SZ500	5	Red	5	STORZ	5 15/32	300	600	900	25/50/100	0.95
JL500TXXX-SZ500	5	Tan	5	STORZ	5 15/32	300	600	900	25/50/100	0.95
JL500WXXX-SZ500	5	White	5	STORZ	5 15/32	300	600	900	25/50/100	0.95
JL500YXXX-SZ500	5	Yellow	5	STORZ	5 15/32	300	600	900	25/50/100	0.95
JL600WXXX-SZ600	6	White	6	STORZ	NA	300	600	900	25/50/100	1.03
JL725WXXX-SZ725	7 1/4	White	7	STORZ	NA	300	600	900	25/50/100	1.11
JL120WXXX-SZ120	12	White	12	STORZ	NA	200	400	600	25/50/100	4.30

\*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.